

DeckHand Portable Scale



STANDARD FEATURES

- Mild or stainless steel frame, base, and mast
- 500 lb, 1,000 lb, 2,000 lb capacity
- Large rubber wheels simplify movement on uneven floors
- Aluminum load cells (2)
- Standard indicator mount with integral handles for the IQ plus® 355, IQ plus 390-DC, IQ plus 510, IQ plus 590-DC, IQ plus 710, and IQ plus 700.

SPECIFICATIONS

End Load Capacity:
100% end loading

mV/V Output:
2 mV/V

Cable length:
9ft 10 in (3 m)

Height:
Weighing platter: 4.5 in H when in weigh mode

Column Height:
59 in

Warranty:
One-year limited warranty

Approvals:
NTEP Certified, CC# 98-004, Class III, 2500d
Measurement Canada approved, AM-5218

APPROVALS



Measurement
Canada
Approved



PART NUMBER/PRICE

PART #	OVERALL SIZE (W X L X H)	CAPACITY	EST. SHIP WEIGHT	PRICE
Mild Steel				
41293	31 in x 41 in x 4.5 in	500 lb	336 lb	Consult
41294	31 in x 41 in x 4.5 in	1,000 lb	356 lb	Consult
41295	31 in x 41 in x 4.5 in	2,000 lb	373 lb	Consult
Stainless Steel				
41296	31 in x 41 in x 4.5 in	500 lb	336 lb	Consult
41297	31 in x 41 in x 4.5 in	1,000 lb	356 lb	Consult
41298	31 in x 41 in x 4.5 in	2,000 lb	373 lb	Consult

OPTIONS/ACCESSORIES

PART #	DESCRIPTION	EST. SHIP WEIGHT	PRICE
89576	Clam shell for 1,260 load cell, stainless steel		Consult
43377	Ramp assembly, 500/1,000 lb, stainless steel, 25 in x 27 in		Consult
43379	Ramp assembly, 2,000 lb, stainless steel, 25 in x 27 in		Consult
N/A	Smooth top		Consult
DeckHand Portable Scale Optional Indicator Mounts			
41371	Mounting bracket for IQ 700 IS, 320IS with battery option stainless steel		Consult

* Approximate weight for scale and indicator

